PITBULL

Compact Loaders

Dear Sir / Madam,

Here's the new Pitbull Compact Loaders catalogue in which Peeters Agricultural Machinery presents its Compact Loaders range. The Pitbull Compact Loader is a unique product with extra attention for safety, quality and power. It's a compact and very versatile machine – perfect for big jobs in small areas.

The high standard of the Pitbull range is guaranteed thanks to the use of the highest quality components. The frame is made from high-quality steel and only A-brand components are used. It is being produced in our new 7,000 m² factory, which uses the very latest equipment, including more than ten robotic systems, to produce high-quality products in the most efficient way possible.

In addition to this Pitbull Compact Loaders catalogue, which is available at www.pitbull-loader.com, the new Peecon Feed Technics, Peecon Manure & Transport Technics and Tulip Agricultural Machinery catalogues are also available online at www.peecon.com and www.tulipindustries.com. You can request extra copies free of charge via info@peetersgroup.com if you wish.

Made in Holland

koninklijke metaalunie

For terms and conditions, please see our website: www.pitbull-loader.com. All prices exclude VAT and delivery. This price list replaces all previous price lists. Subject to changes and printing errors.

Index

Features

Page 7

Details

Page 8-9

Specifications

Page 12-13

Pitbull X24 serie

Page 14-15

Pitbull X27 serie

Page 18-19

Tyres options

Page 22-23


Stainless steel hoods
ROPS/FOPS safety roof
4 cylinder
Kubota engine
Unique P-Z boom
12.000 kg
Dana Spicer axles
Standard hydraulic quick-change
Wide range of tyres
Rigid pivoting point
combined with rocking rear
axle provides stability
450 Bar Linde high-pressured
hydraulic system

01 P-Z boom
Due to the unique construction of the boom with a combination of P- and Z-kinematics the boom has a high breakout force and optimum parallel guidance.

02 Fall protection
The telescopic fall protection stays within the machine width at all times, preventing unnecessary damage.

03 Rocking axle
The rigid pivoting point in combination with the rocking rear axle make the Pitbull very stable and suitable for working on uneven surfaces.

04 Maintenance
All the maintenance that has to be done on a regular base is easy to do. All the filters which need to be cleaned are within reach when the hoods are opened.

05 Axles
The very strong 12.000 kg Dana Spicer axles are able to carry over 3 times the weight of the Pitbull. This provides maximum capacity and an extended lifetime of the axles.

06 Motor
The 4 cylinder Kubota V1505 motor is the heart of the Pitbull. Standard this engine provides 36 HP, the turbo version even provides 45 HP.

PITBULL
PITBULL
PITBULL



		X24-36	X24-45	X27-36	X27-45
Wheelbase (A)	mm	1624	1624	1624	1624
Length without bucket (B)	mm	3100	3100	3150	3150
Length with bucket (C)	mm	3620	3620	3670	3670
Seat top height (D)*	mm	1240	1240	1240	1240
Total height (E)*	mm	2140	2140	2140	2140
Max. dumping height (F)*	mm	2250	2250	2250	2250
Max. height with bucket (G)*	mm	3270	3270	3270	3270
Max. height pivot (H)*	mm	2830	2830	2830	2830
Diameter standard tyre (I)*	mm	800	800	800	800
Undermining (J)*	mm	30	30	30	30
Rollback angle (K)	°	50	50	50	50
Dumping angle (L)	°	38	38	38	38
Max. drive up angle (M)	°	35	35	35	35
Min. machine width (N)	mm	1220/1500	1220/1500	1220/1500	1220/1500
Weight	kg	2400	2400	2700	2700
Lifting capacity	kg	1800	1800	2300	2300
Outer radius (without bucket)	mm	2600	2600	2600	2600

* With standard tire

The X24 series: A compact helping hand

The X24 series are stable, flexible and very compact wheel loaders. This model is extremely suitable for working in old stables or when low areas have to be passed. Due to its compact and light weight design this model is extremely suitable to be used at any location. The low weight of the machine makes sure there is no limmits on transport of the machine.

Standard equipment

- 12.000 kg Dana Spicer axles with 45 % differential blocking on the front and rear axle
- X24 - 36: Drive motor with fixed stroke volume
  X24 - 45: Variable drive motor
- Cardan shaft with disc brake
- Hydrostatic transmission
- 450 Bar Linde high-pressured system
- Working hydraulics: max. 50 l/min
- Hydraulic quick-change
- IBT cooler
- ROPS/FOPS safety roof
- Trelleborg 400/50-15 T463 tyres
- Painted in Pitbull red, chassis in Pitbull grey



Article number	Standard equipment
450-240-001	**X24 - 36**
	Kubota 4 cylinder motor - forward driving speed 0-18 km/h

Article number	Standard equipment
450-240-002	**X24 - 45**
	Kubota 4 cylinder motor with Turbo - forward driving speed 0-27 km/h

Article number	Optional equipment
450-908-002	100% Differential blocking of the front axle with open-end differential on the rear axle instead of 2x 45% Differential blocking switchable / integrated oil slat brakes in the front axle / electric handbrake
450-908-003-001	3th Hydraulic function in front, manually switchable (not in combination with 450-908-003-002)
450-908-003-002	3th Hydraulic function in front, electric switchable using the steering column (not in combination with 450-908-003-001)
450-908-003-003	4th Hydraulic function in front (not in combination with 450-908-003-004)
450-908-003-004	Hydraulic function at the back (not in combination with 450-908-003-003)
450-908-004-001	Pressure-free oil return in front (not in combination with 450-908-004-002)
450-908-004-002	Pressure-free oil return at the back (not in combination with 450-908-004-001)
450-908-005	Different attachment from standard
450-908-006	Inching, control on the joystick
450-908-010	Halogen lighting set
450-908-007	LED lighting set
450-908-008	LED beam in front
450-908-009	LED working lights left and right at the back
450-908-011	Flashing light
450-908-012	Mirrors
450-908-013	Package for road admission (RDW / PVG / TÜV)
450-908-014	Front and back window mounted on ROPS/FOPS safety roof
450-908-015-001	Towing hook, ball
450-908-015-002	Combi towing hook, ball and pin
450-908-021	Pallet forks
450-908-033	Stone bucket
450-908-037	Bucket
450-908-016	12 Volt connection for trailer lighting at the back
450-908-017	Locks on the hoods
450-908-018	Fuel cap with lock
450-908-019	100 Kg extra weight added to the back
450-908-020-...	Other RAL colour instead of Pitbull red (yellow RAL 1023 / blue RAL 5009 / green RAL 6002)
450-908-036	Other RAL colour instead of Pitbull red (and different from option 450-908-020-...)
	Optional tyres (price per 4 and instead of standard tyre)
450-908-023	Alliance 31x15.50 - 15 NHS 221
450-908-024	Mitas 31x15.5 - 15 SK-02
450-908-025	Mitas 31x15.50 - 15 TR-06
450-908-026	Mitas 440/50 R17 IMP AR-04
450-908-027	Vredestein 400/60 - 15.5 IMP
450-908-028	BKT 19.0/45-17 AS504
450-908-035	Deestone 31x15.50 - 15 NHS
450-908-029	Alliance 31x15.50 - 15 NHS 223
450-908-030	Mitas 31x15.50 - 15 TR-07
450-908-031	Mitas 425/55 R17 MPT AC70 G
450-908-032	Mitas 480 45-17 IMP TR-01
	Other tyres

PITBULL
PITBULL
PITBULL

The X27 series: A powerful all-rounder

The X27 series are stable, flexible and very comfortable wheel loaders. The machine is suitable for the user who has to hop on and off the machine a lot because of the possibility to enter the machine from both sides. The strength in combination with the accessibility and comfort makes the X27 the ideal all-rounder.

Standard equipment

- 12.000 kg Dana Spicer axles with 100% Differential blocking of the front axle with open-end differential on the rear axle
- Differential blocking switchable / integrated oil slat brakes in the front axle / electric handbrake
- X27 - 36: Drive motor with fixed stroke volume
  X27 - 45: Variable drive motor
- Cardan shaft
- Hydrostatic transmission
- 450 Bar Linde high-pressured system
- Working hydraulics: max. 50 l/min
- Hydraulic quick-change
- IBT cooler
- Bucket
- ROPS/FOPS safety roof
- Trelleborg 400/50-15 T463 tyres
- Painted in Pitbull red, chassis in Pitbull grey



Article number	Standard equipment
450-270-001	**X27 - 36**
	Kubota 4 cylinder motor - forward driving speed 0-18 km/h

Article number	Standard equipment
450-270-002	**X27 - 45**
	Kubota 4 cylinder motor with Turbo - forward driving speed 0-27 km/h

Article number	Optional equipment
450-908-038	2x 45% differential blocking instead of 100 % of the front axle with open-end differential on the rear axle Fixed differential blocking / disc brake on cardan shaft / manually handbrake
450-908-003-001	3th Hydraulic function in front, manually switchable (not in combination with 450-908-003-002)
450-908-003-002	3th Hydraulic function in front, electric switchable using the steering column (not in combination with 450-908-003-001)
450-908-003-003	4th Hydraulic function in front (not in combination with 450-908-003-004)
450-908-003-004	Hydraulic function at the back (not in combination with 450-908-003-003)
450-908-004-001	Pressure-free oil return in front (not in combination with 450-908-004-002)
450-908-004-002	Pressure-free oil return at the back (not in combination with 450-908-004-001)
450-908-005	Different attachment from standard
450-908-006	Inching, control on the joystick
450-908-010	Halogen lighting set
450-908-007	LED lighting set
450-908-008	LED beam in front
450-908-009	LED working lights left and right at the back
450-908-011	Flashing light
450-908-012	Mirrors
450-908-013	Package for road admission (RDW / PVG / TÜV)
450-908-014	Front and back window mounted on ROPS/FOPS safety roof
450-908-015-001	Towing hook, ball
450-908-015-002	Combi towing hook, ball and pin
450-908-021	Pallet forks
450-908-033	Stone bucket
450-908-016	12 Volt connection for trailer lighting at the back
450-908-017	Locks on the hoods
450-908-018	Fuel cap with lock
450-908-034	100 Kg less weight
450-908-020-...	Other RAL colour instead of Pitbull red (yellow RAL 1023 / blue RAL 5009 / green RAL 6002)
450-908-036	Other RAL colour instead of Pitbull red (and different from option 450-908-020-...)
	Optional tyres (price per 4 and instead of standard tyre)
450-908-023	Alliance 31x15.50 - 15 NHS 221
450-908-024	Mitas 31x15.5 - 15 SK-02
450-908-025	Mitas 31x15.50 - 15 TR-06
450-908-026	Mitas 440/50 R17 IMP AR-04
450-908-027	Vredestein 400/60 - 15.5 IMP
450-908-028	BKT 19.0/45-17 AS504
450-908-035	Deestone 31x15.50 - 15 NHS
450-908-029	Alliance 31x15.50 - 15 NHS 223
450-908-030	Mitas 31x15.50 - 15 TR-07
450-908-031	Mitas 425/55 R17 MPT AC70 G
450-908-032	Mitas 480 45-17 IMP TR-01
	Other tyres

PITBULL
PITBULL
PITBULL
X27-45
PITBULL

Alliance 31x15.50 - 15 NHS 221

Mitas 31x15.5 - 15 SK-02

Mitas 31x15.50 - 15 TR-06

Mitas 440/50 R17 IMP AR-04

Sizes of the machine may change when different tyres are chosen.

Vredestein 400/60 - 15.5 IMP

The right tyre for each surface

BKT 19.0/45-17 AS504

Deestone 31x15.50 - 15 NHS

Alliance 31x15.50 - 15 NHS 223

Mitas 31x15.50 - 15 TR-07

Mitas 425/55 R17 MPT AC70 G

Mitas 480 45-17 IMP TR-01

Request our other catalogues free of charge for Peecon Feed Technics, Peecon Manure- & Transport Technics and Tulip Arable Machinery

PEETERS LANDBOUWMACHINES B.V.
Manufacturer of Pitbull Compact Loaders

Munnikenheiweg 47
4879 NE Etten-Leur (The Netherlands)

Tel.: +31 (0)76-5046666

info@pitbull-loader.com
www.pitbull-loader.com
www.facebook.com/pitbull-loader

956-170-001-001 / 2019-09 EN

Would you like more information about our products? Please contact us or visit our website: **www.peetersgroup.com**

PEETERS
LANDBOUWMACHINES